SHANNON 6030

STUDIO COLLECTION



PVC SYSTEMS INCLUDE:

- 6 Fully directional adjustable PVC jets
- Anti-vortex safety suction
- Color matched system trim
- Rigid PVC piping
- Self draining pump and system
- Air switch control
- 1.25 HP single speed pump
- Requires 120 V 15 Amp Dedicated **GFCI**



OPTIONS: (MORE INFORMATION AVAILABLE ON OUR WEBSITE)

- Custom jet and pump locations
- Integral waste and overflow (round)
- In-line heater
- Hydro Coat
- Hydro Express quick ship

- Cable Waste and Overflow
- Hydrozone

STANDARD ELECTRICAL REQUIREMENTS:

- Whirlpool System | One 20 Amp Dedicated Circuit
- Thermal Air System I One 15 Amp Dedicated Circuit
- Inline Heater (600 or 1500 Watts) | One 15 Amp Dedicated Circuit

All electrical components come standard at 115 volts

All electrical circuits must be GFCI protected

SHANNON 6030

STUDIO COLLECTION



As Shown:

Whirlpool option with standard jet location

FEATURES SHOWN:

- Jets
- Overflow location
- Flange on Skirt

ALSO AVAILABLE:

- Soaking tub only
- Thermal Air

WATER CAPACITY:

60 Gallons

BACK SLOPE:

28 Degrees

WEIGHT:

90 - 110 Pounds


3-Wall Installation Dimensions:


Opening (L)ength - 60" Opening (W)idth - 30" Ledger- 19-3/4"



ACRYLIC TUB

- Model comes with integral tile flange and skirt
- Extra thick reinforced fiberglass
- Pre-wired pump on pump platform (standard pump location only)
- Integral E-Z level platform facilitates installation
- Tub must be set in a mortar base





CODES AND COMPLIANCES

Massachusetts code File no: P1-0614-491
















Page 2 of 2 MADE IN AMERICA