



Standard Grab Bar



Linear Integral Waste and Overflow



OPTIONS: (MORE INFORMATION AVAILABLE ON OUR WEBSITE)

- Chromatherapy-LED Lighting System
- Cold Plunge
- Extra High Density
- Grab Bars
 - Standard or Universal
- Hydro Blanket
- Hydro Coat
- Hydro Fusion

- Hydro Indulge
- Hydro Express Quick Ship
- Island Tub Drain
- Integral Waste and Overflow
 - Linear
- Padded Headrest Pillow
- Remote Control System

STANDARD ELECTRICAL REQUIREMENTS:

• Thermal Air System I One 15 Amp Dedicated Circuit

All electrical components come standard at 115 volts

All electrical circuits must be GFCI protected







As Shown:

• Tub Only

ALSO AVAILABLE:

• Thermal Air

BACKSLOPE:

• 30 degrees

WATER CAPACITY:

• 110 gallons

WEIGHT:

• 150 - 180 lbs depending on system


DIMENSIONS:


- (L)ength- 70"
- (W)idth- 40"
- (H)eight- 28-1/2"



ACRYLIC TUB

- Acrylic models finished in 1/8" thick layer of deep lustrous acrylic
- Integral E-Z level platform facilitates installation
- Extra thick reinforced fiberglass





CODES AND COMPLIANCES

Massachusetts code File no: P1-0614-491











