ELLE 6632

DESIGNER COLLECTION

HS

PVC Systems Include:

- 6 Fully directional adjustable flow PVC jets
- Anti-vortex safety suction
- Color matched system trim
- HydroOzone ozone sanitation system
- Rigid PVC piping
- Self draining pump and system
- Soft Touch electronic on/off control with 30-minute integral times
- 2.25 HP single speed pump
- Cable waste and overflow









OPTIONS: (MORE INFORMATION AVAILABLE ON OUR WEBSITE)

- Additional Jets
 - Directional or Swirling
- Back Masseuse Systems
- Chromatherapy-LED Lighting System
- Custom Jet and Pump Location
- Electronic Low Water Protection
- Extra High Density
- Faucet Deck
- Grab Bars
 - Standard or Universal
- Hydro Coat
- Hydro Express Quick Ship

- Hydro Fusion
- Hydro Indulge
- HydrOzone UV System
- In-line Heater
- Integral Waste and Overflow
 - Round or Linear
- Jumbo Jets
 - Directional or Rotating
- Micro Mount
- Micro Therapy Jets
- Molded Armrests
- Neck Masseuse Pillow

STANDARD ELECTRICAL REQUIREMENTS:

- Whirlpool System | One 20 Amp Dedicated Circuit
- Thermal Air System | One 15 Amp Dedicated Circuit
- Combo System I One 15 Amp Dedicated Circuit and One 20 Amp Dedicated Circuit
- Indulge System I One 15 Amp Dedicated Circuit
- Hydro Fusion (600 or 1500 Watts) | One 15 Amp Dedicated Circuit
- Inline Heater (600 or 1500 Watts) | One 15 Amp Dedicated Circuit

All electrical components come standard at 115 volts

All electrical circuits must be GFCI protected



ELLE 6632

HIS

DESIGNER COLLECTION

As Shown:

Whirlpool option with standard jet location

FEATURES SHOWN:

- Jets
- Overflow location
- Drain location

ALSO AVAILABLE:

- · Soaking tub only
- Whirlpool
- Thermal Air
- Combo

SIZE:

66.32.18

WATER CAPACITY:

45 Gallons

WEIGHT:

70-110 Pounds

DROP-IN CUTOUT INSTALL DIMENSIONS:

- (L)ength 64"
- (W)idth 30"
- Finished Height 18-1/4"

INSTALLATION TIPS:


- When adding integral linear drain p-trap location is now below waste
- Adding multiple systems/options may require equipment to stick out from tub deck or be installed remotely


ACRYLIC TUB

- Acrylic models finished in 1/8" thick layer of deep lustrous acrylic
- Pre-wired pump on pump platform (standard pump location only)
- Integral E-Z level platform facilitates installation
- Micro mount reduces lip height by approximately 3/8" to 5/8"
- Micro mount requires increase in framing height by approximately 1-1/4"

STREET

33 32 32 35 3





CODES AND COMPLIANCES

Massachusetts code File no: P1-0614-491 16.5







HYDRO SYSTEMS

Family Owned And Operated Since 1978





