

CARRERA 7236



STON COLLECTION

PVC SYSTEMS INCLUDE:

- 8 Fully directional adjustable flow PVC jets
- Anti-vortex safety suction
- Color matched system trim
- HydroOzone ozone sanitation system
- Rigid PVC piping
- Self draining pump and system
- Soft Touch electronic on/off control with 30-minute integral times
- 2.25 HP single speed pump
- Cable waste and overflow



Standard Grab Bar



Linear Integral Waste and Overflow



Chromotherapy-LED Lighting System

OPTIONS: [\(MORE INFORMATION AVAILABLE ON OUR WEBSITE\)](#)

- Additional Jets
 - Directional or Swirling
- Back Masseur Systems
- Chromotherapy-LED Lighting System
- Custom Jet and Pump Location
- Electronic Low Water Protection
- Grab Bars
 - Standard or Universal
- Hydro Coat
- Hydro Express Quick Ship
- Hydro Fusion
- Hydro Indulge
- HydroOzone UV System
- In-line Heater
- Integral Waste and Overflow
 - Round or Linear
- Jumbo Jets
 - Directional or Rotating
- Micro Mount
- Micro Therapy Jets
- Neck Masseur Pillow
- Remote Control System
- Skirt (1-4 sides)
- Tile Flanges

STANDARD ELECTRICAL REQUIREMENTS:

- Whirlpool System | One 20 Amp Dedicated Circuit
- Thermal Air System | One 15 Amp Dedicated Circuit
- Combo System | One 15 Amp Dedicated Circuit and One 20 Amp Dedicated Circuit
- Indulge System | One 15 Amp Dedicated Circuit
- Hydro Fusion (600 or 1500 Watts) | One 15 Amp Dedicated Circuit
- In-line Heater (600 or 1500 Watts) | One 15 Amp Dedicated Circuit

All electrical components come standard at 115 volts

All electrical circuits must be GFCI protected

CARRERA 7236



STON COLLECTION

As SHOWN:
Whirlpool option

- FEATURES SHOWN:
- Overflow location
 - Standard jet location

- ALSO AVAILABLE:
- Soaking tub only
 - Thermal Air
 - Combo

BACKSLOPE:
24 degrees

WATER CAPACITY:
95 Gallons

WEIGHT:
190-230 Pounds depending on system

- DROP-IN INSTALLATION DIMENSIONS:
- (L)ength- 70"
 - (W)idth- 34"
 - (H)eight- 22-1/2"


- INSTALLATION TIPS:
- When adding integral linear drain p-trap location is now below waste
 - Adding multiple systems/options may require equipment to stick out from tub deck or be installed remotely



Tub must be set in mortar base


Hydroluxe SS Tub

- Hydroluxe SS model finished in 1-2" thick solid surface material
- Pre-wired pump on pump platform (standard pump location only)
- Micro mount reduces standard edge height of tub to minus (-) 3/8 to 5/8"



Thermal Air inlet location and quantity are not precise and are for reference only

- Optional Equipment Dimensions
- Whirlpool Pump: 12"(H) x 16"(L)
 - Thermal Air Blower: 5"(H) x 11"(L)
 - Hydro Fusion: 7"(H) x 15.5"(L)
 - Hydro Indulge: 11"(H) x 19"(L)



CODES AND COMPLIANCES
Massachusetts code File no: P1-0614-491



HYDRO SYSTEMS
Family Owned And Operated Since 1978

29132 Avenue Paine, Valencia, CA, 91355
661.775.0686 | hydrosystem.com

All specifications and options subject to change without notice please contact a Hydro Systems representative for more information. Certain options or altering the pump/blower location may cause the pump/blower to extend beyond the tub decking. For cutout dimensions wait for unit to arrive. All specifications subject to change without notice.